

Ensis DW 6062

Long term rust preventive with dewatering properties

DESCRIPTION

Ensis DW 6062 is a long term rust protective, suitable for metal surfaces likely to corrode in storage or use.

Ensis DW 6062 is a water-displacing, solvent based rust inhibitor that leaves a temporary waxy protective film on metal surfaces. The product protects metal parts from the damaging effects of moisture, air, detergents and other contaminants.

APPLICATION

Ensis DW 6062 can be applied by dipping and brushing.

After the evaporation of the solvent, Ensis DW 6062 leaves a waxy protective film on surfaces. Ensis DW 6062 is easily removed with aqueous alkaline cleaners or solvents. It is a premium quality, dewatering type rust preventive with good coverage. Effective in neutralizing finger prints. Resists cracking & peeling.

Use Ensis DW 6062 where excellent covering capacity and long-term protection is required.

RECOMMENDATIONS FOR USE

Ensis DW 6062 is used neat as supplied.

TYPICAL PHYSICAL PROPERTIES

TEST	TYPICAL VALUE	TEST METHOD
Appearance	Brown oil	
Specific gravity @ 20 °C	0.876	ASTM D 4052
Flash Point PMCC °C	72	ASTM D 93
Film thickness µm	App. 60	
Classification ISO 6743-8	ISO L-RFF/RM	

ADVANTAGES

- ❑ Indoor protection 60 months
- ❑ Covered outdoors 24 months
- ❑ Outdoors uncovered up to 12 months
- ❑ Easily removed with alkaline or solvent based cleaners
- ❑ Dry waxy film

STORAGE

Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is between 5°C and 35°C. Use stock in delivery rotation. A shelf life of twenty four months can be anticipated.

HEALTH AND SAFETY

Health and Safety Data Sheets are supplied to customers to comply with Section 6 of the Health and Safety at Work Act 1974, and should be closely studied prior to handling or use of the product. Copies are available from your Technical Health and Safety Officer. Various other advisory publications are available from the Health and Safety Executive and Her Majesty's Stationery Office.

05/11

All data given in this Product Data Sheet are typical of this material. It does not however constitute a specification. We reserve the right to modify products without prior notice. All products, services and information supplied are provided upon the terms of our standard Conditions of Sale from time to time in force.

Houghton plc

Beacon Road Trafford Park Manchester M17 1AF

Tel +44 (0) 161 874 5000

Fax +44 (0) 161 874 5001

E-mail uk.enquiries@houghtoneurope.com



HOUGHTON